

# Fuga-Soap

Detergent for removing streaks of Fugalite.

Fuga-Soap is an effective and specific detergent for use in cleaning after laying as well as in the routine maintenance of ceramic tiles, porcelain tiles and natural stones.



1. Floors and walls
2. Suitable for use with compact and porous materials
3. Suitable for delicate marbles
4. Ideal also for domestic environments

---

## Areas of application

→ Use  
Cleaning of residues and streaks of Fugalite Color and Fugalite Invisible from ceramic surfaces.

Substrates:

- ceramic, porcelain tiles
- glass mosaic, marble and natural stone

Do not use surfaces that are not resistant to basic agents.

---

## Instructions for use

→ Preparation of substrates  
Fugalite Color and Fugalite Invisible must be fully hardened. The coating materials must first be cleaned to remove any dust.

→ Preparation  
Fuga-Soap is a ready-to-use yellowish liquid that can be diluted using water.  
Shake the bottle well before opening in order to redisperse the liquid evenly.  
Dilute 1:1 to 1:3 using warm water depending on the type of dirt to be removed.

→ Application  
It is advisable to perform a preliminary test on tiles that are not to be laid, or in a concealed area. Apply Fuga-Soap evenly to the surface to be cleaned with a white rough scrubbing pad

and leave it until the dirt to be removed begins to visibly lift; this may take a few minutes or up to 10 – 15 minutes depending on the quantity, the elapsed time after laying (at least 24 hours) and the degree of absorption of the surface. Scrape the surface mechanically with abrasive felt pads. Once cleaned, rinse well and dry carefully. The use of wet vacuum makes the operation easier and ensures the complete removal of residue. In the case of large surface areas, a mechanical buffer with an abrasive felt pad for the removing operation is recommended. Repeat for highly stubborn dirt.

→ Cleaning  
Residual traces of Fuga-Soap can be removed from tools with water.

---

## Special notes

→ Fuga-Soap is a liquid detergent. Before using the product, it is advisable to hermetically seal all doors, windows, rubber seals, furniture, varnished/painted elements, bathtubs and

shower trays made of synthetic materials such as methacrylate, PVC, etc. and any surface that could be attacked through direct contact with the detergent or with vapours.

---

## Abstract

*Streaks of Fugalite Color and Fugalite Invisible from ceramic tiles, porcelain tiles, glass mosaic, marble and natural stones will be cleaned with a water-based detergent, such as Fuga-Soap by Kerakoll Spa. Apply evenly to the surface to be treated, remove dirt with mechanical means and rinse thoroughly, and dry carefully, for an average coverage of 1 l = 20 – 40 m<sup>2</sup>.*


**Technical Data compliant with Kerakoll Quality Standard**

|   |  |                   |
|---|--|-------------------|
| Appearance                              | yellowish liquid   |                   |
| Specific weight                         | ≈ 1.01 kg/dm <sup>3</sup>  |                   |
| Shelf life                              | ≈ 24 months from production in the original sealed packaging                             |                   |
| Warning                                 | protect from frost, avoid direct exposure to sunlight and sources of heat                |                   |
| Pack                                    | 1 l bottles  |                   |
| Water dilution ratios                   | from 1:1 to 1:3  |                   |
| Viscosity                               | ≈ 211 mPa · s, rotor 2 RPM 50  | Brookfield method |
| pH                                      | ≈ 12.5   |                   |
| Temperature range for application       | from +5 °C to +35 °C   |                   |
| Waiting time before cleaning with water | ≈ 10 – 30 min.   |                   |
| Coverage                                | ≈ 20 m <sup>2</sup> /1 l with 1:1 dilution<br>≈ 40 m <sup>2</sup> /1 l with 1:3 dilution |                   |

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate and of the materials laid.

## Warning

- Abide by any standards and national regulations
  - store and use at a temperature above +5 °C. Protect from frost
  - rinse thoroughly all surfaces treated
  - do not leave cans or bottles open, even during use
- if necessary, ask for the safety data sheet
  - for any other issues, contact Kerakoll Technical Customer Service: + 39 0536.811.516  
[www.kerakoll.com/contatti](http://www.kerakoll.com/contatti)



This information was last updated in May 2026; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.